

SAFETY AND BUILDINGS DIVISION
Plumbing Product Review
P.O. Box 2658
Madison, Wisconsin 53701-2658
TTY: Contact Through Relay

Jim Doyle, Governor Richard J. Leinenkugel, Secretary

October 20, 2009

LEWIS-PIPE COMPANY PAUL COBLE

PO BOX 339 ARDMORE TN 38449

Re: Description: PIPES AND FITTINGS, CPVC

Manufacturer: LEWIS-PIPE COMPANY

Product Name: CPVC SCH 80

Model Number(s): P-S-1204, P-S-1604, P-S-2404

Product File No: 20090376

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters Comm 82 through 84, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an alternate approval to s. Comm 84.30 (4) (e) 1. based on the Wisconsin Statutes and the Wisconsin Administrative Code. This approval is valid until the end of October 2014.

This alternate approval is contingent upon compliance with the following stipulation(s):

- Piping shall be labeled at intervals of not more than 5 feet with nominal pipe size, type of pipe material, Schedule 80, pressure rating in psi at 73 degrees F., ASTM F 441 and/or F 441M, the manufacturer's name or trade mark, the mark of the certifying agency for use with potable water.
- This product may be installed for the following water use(s):
 - a. Cold water distribution piping Aboveground
 - b. Cold water distribution piping Underground
- Pipe sizing for this product must comply with Table Lewis-Pipe Company Sch. 80 CPVC Pipe. Table notes: WSFU means water supply fixture units, GPM means gallons per minute, FM means predominately flushometer type water closets or siphon jet urinals, FT means predominately flush tank type water closets or wash down urinals, and NP means not permitted.

SBD-10564-E (N.10/97) File Ref: 09037604.DOC

Table for Lewis-Pipe Co. Sch 80 CPVC Pipe Maximum Allowable Load for Lewis Blue CPVC, Sch. 80; (C=150)

Pressure	Pipe Diameter (in Inches)									
Loss Due to Friction (in lbs. per	3				4			6		
100 ft. of		WSFU			WSFU			WSFU		
Length	GPM	FM	FT	GPM	FM	FT	GPM		FT	
0.25	40	30	86	84	165	295	247	1315	1315	
0.5	58	70	225	122	375	485	359	2352	2352	
0.75	72	126	240	151	560	646	447	3161	3161	
1	84	165	295	177	754	794	522	3966	3966	
1.25	95	217	350	199	918	931	589	4941	4941	
1.5	105	272	400	220	1094	1094	NP			
1.75	114	325	445	239						
2	123	381	490	257						
2.25	131	431	533	274						
2.5	138	475	572	NP						
2.75	146	527	617							
3	153	572	655							
3.25	NP									

Notes: NP means Not Permitted

The department is in no way endorsing this product or any advertising, and is not responsible for any situation which may result from its use.

Sincerely,

Jerry Thompson Plumbing Product Reviewer Phone: 608-266-6742

Fax: 608-267-9566

E-mail: jerry.thompson@wi.gov

^{*} means that WSFU must be determined by calculations